

**TO-92L Plastic-Encapsulate Transistors****2SA1020** TRANSISTOR (PNP)**FEATURES**

Power amplifier applications

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)


Symbol	Parameter	Value	Units
V_{CBO}	Collector-Base Voltage	-50	V
V_{CEO}	Collector-Emitter Voltage	-50	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_{C}	Collector Current –Continuous	-2	A
P_{C}	Collector Power Dissipation	900	mW
T_{J}	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature	-55-150	$^{\circ}\text{C}$

TO-92L

1. EMITTER

2. COLLECTOR

3. BASE

**ELECTRICAL CHARACTERISTICS** ($T_{\text{amb}}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(\text{BR})\text{CBO}}$	$I_{\text{C}}=-100\mu\text{A}, I_{\text{E}}=0$	-50			V
Collector-emitter breakdown voltage	$V_{(\text{BR})\text{CEO}}$	$I_{\text{C}}=-10\text{mA}, I_{\text{B}}=0$	-50			V
Emitter-base breakdown voltage	$V_{(\text{BR})\text{EBO}}$	$I_{\text{E}}=-100\mu\text{A}, I_{\text{C}}=0$	-5			V
Collector cut-off current	I_{CBO}	$V_{\text{CB}}=-50\text{V}, I_{\text{E}}=0$			-1	μA
Emitter cut-off current	I_{EBO}	$V_{\text{EB}}=-5\text{V}, I_{\text{C}}=0$			-1	μA
DC current gain	$h_{\text{FE}(1)}$	$V_{\text{CE}}=-2\text{V}, I_{\text{C}}=-0.5\text{A}$	70		240	
	$h_{\text{FE}(2)}$	$V_{\text{CE}}=-2\text{V}, I_{\text{C}}=-1.5\text{A}$	40			
Collector-emitter saturation voltage	$V_{\text{CE(sat)}}$	$I_{\text{C}}=-1\text{A}, I_{\text{B}}=-50\text{mA}$			-0.5	V
Base-emitter saturation voltage	$V_{\text{BE(sat)}}$	$I_{\text{C}}=-1\text{A}, I_{\text{B}}=-50\text{mA}$			-1.2	V
Transition frequency	f_{T}	$V_{\text{CE}}=-2\text{V}, I_{\text{C}}=-500\text{mA}$		100		MHz
Collector output capacitance	C_{ob}	$V_{\text{CB}}=-10\text{V}, I_{\text{E}}=0, f=1\text{MHz}$		40		pF
Turn-on time	t_{on}	$V_{\text{CC}}=-30\text{V}, I_{\text{B1}}=-I_{\text{B2}}=-0.05\text{A}, I_{\text{C}}=-1\text{A}$		0.1		μs
Storage time	t_{s}			1		μs
Fall time	t_{f}			0.1		μs

CLASSIFICATION OF $h_{\text{FE}(1)}$

Rank	O	Y
Range	70-140	120-240

Typical Characteristics

2SA1020

