

**SOT-23 Plastic-Encapsulate Transistors****2SC5344** TRANSISTOR (NPN)**FEATURES**

Power dissipation

 P_{CM} : 0.2 W ($T_{amb}=25^{\circ}C$)

Collector current

 I_{CM} : 0.8 A

Collector-base voltage

 $V_{(BR)CBO}$: 35 V


Operating and storage junction temperature range

 T_J, T_{stg} : $-55^{\circ}C$ to $+150^{\circ}C$ **SOT—23**

1. BASE

2. EMITTER

3. COLLECTOR



Unit: mm

ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu A, I_E=0$	35			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=35V, I_E=0$			0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=5V, I_C=0$			0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=1V, I_C=100mA$	100		320	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=500mA, I_B=50mA$			0.5	V
Transition frequency	f_T	$V_{CE}=5V, I_C=10mA$		120		MHz
Collector output capacitance	C_{ob}	$V_{CB}=10V, I_E=0, f=1MHz$		13		pF

CLASSIFICATION OF $h_{FE(1)}$

Rank	O	Y
Range	100-200	160-320
Marking	FAO	FAY