



JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

WBFBP-03D Plastic-Encapsulate DIODE

DK914LLD03

SWITCHING DIODE

DESCRIPTION

Epitaxial planar Silicon diode

FEATURES


Fast Switching Speed

Ultra-Small Surface Mount Package

For General Purpose Switching Applications

High Conductance

Lead Free Product




APPLICATION


High Conductance Ultra Fast Diode

For portable equipment:(i.e. Mobile phone,MP3, MD,CD-ROM, DVD-ROM, Note book PC, etc.)

MARKING: 5D



+ NC



Maximum Ratings and Electrical Characteristics, Single Diode @T_A=25°C

Parameter	Symbol	Limite	Unit
Non-Repetitive Peak reverse voltage	V _{RM}	100	V
Peak Repetitive Peak reverse Voltage	V _{RRM}	100	V
Working Peak Reverse Voltage	V _{RWM}		
DC Blocking Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	53	V
Forward Continuous Current	I _{FM}	500	mA
Average Rectified Output Current	I _O	300	mA
Power Dissipation	P _D	100	mW
Junction temperature	T _j	125	°C
Storage temperature	T _{STG}	-55~+150	°C

Electrical Ratings @T_A=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit.	Conditions
Forward voltage	V _{F1}			0.715	V	I _F =1mA
	V _{F2}			0.855	V	I _F =10mA
	V _{F3}			1.0	V	I _F =50mA
	V _{F4}			1.25	V	I _F =150mA
Reverse current	I _{R1}			1	μA	V _R =75V
	I _{R2}			25	nA	V _R =20V
Capacitance between terminals	C _T			2	pF	V _R =0,f=1MHz
Reverse Recovery Time	t _{rr}			4	ns	I _F =I _R =10mA,I _{rr} =0.1X I _R

Typical Characteristics

DK914LLD03




Figure 1. Forward Voltage




Figure 2. Leakage Current




Figure 3. Capacitance