

FR3A THRU FR3M

SURFACE MOUNT FAST RECOVERY RECTIFIER



康 比 電 子
HORNBY ELECTRONIC

REVERSE VOLTAGE: 50 to 1000 VOLTS

FORWARD CURRENT: 3.0 AMPERE

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- For surface mounted applications
- Low profile package
- Easy pick and place
- Built-in strain relief
- Fast Recovery times for high efficiency
- High temperature soldering : 250°C /10 seconds at terminals

MECHANICAL DATA

Case: Molded plastic, DO-214AB(SMC)



Terminals: Solder plated, solderable per MIL-STD-750, method 2026 guaranteed

Polarity: Color band denotes cathode end

Packaging: 16mm tape per EIA STD RS-481

Weight: 0.007 ounce, 0.21 gram

DO214-AB(SMC)



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

	Symbols	FR3A	FR3B	FR3D	FR3G	FR3J	FR3K	FR3M	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current at T _L =75℃	I _(AV)	3.0							Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	100							Amp
Maximum Forward Voltage at 3.0A	V _F	1.3							Volts
Maximum Reverse Current at T _A =25℃ at Rated DC Blocking Voltage T _A =125℃	I _R	5.0 300							μAmp
Typical Junction Capacitance (Note 1)	C _J	60							pF
Typical Thermal Resistance (Note 2)	R _{θJA}	50							℃/W
	R _{θJL}	15							
Maximum Reverse Recovery Time (Note 3)	T _{RR}	150				250	500		nS
Operating Junction Temperature Range	T _J	-55 to +150							℃
Storage Temperature Range	T _{stg}	-55 to +150							℃

NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3 x 0.3" (8.0 x 8.0mm) copper pad areas

3- Reverse Recovery Test Conditions: $I_F=5A$, $I_R=1A$, $I_{RR}=25A$.

FR3A THRU FR3M

SURFACE MOUNT FAST RECOVERY RECTIFIER

RATINGS AND CHARACTERISTIC CURVES




Fig.1-REVERSERECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




Fig.2-MAXIMUM NON-REPEITIVE SURGE CURRENT




Fig.3-MAXIMU AVERAGE FORWARD CURRENT RATING




Fig.4- FORWARD CURRENT DERATING CURV




Fig. 5-TYPICAL REVERSE CHARACTERISTICS




Fig.6- TYPICAL JUNCTION CAPACITANC