

HER601 THRU HER608
HIGH EFFICIENCY RECTIFIER




REVERSE VOLTAGE: 50 to 1000 VOLTS
FORWARD CURRENT: 6.0 AMPERE

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound.
- Void-free Plastic in a R-6 package.
- 6.0 ampere operation at T_A=55°C With no thermal runaway.
- Ultra Fast switching for high efficiency.
- Exceeds environmental standards of MIL-S-19500/228

MECHANICAL DATA

Case: Molded plastic, R-6
Terminals: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
Polarity: Band denotes cathode
Mounting position: Any
Weight: 0.07ounce, 2.1gram



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

	Symbols	HER601	HER602	HER603	HER604	HER605	HER606	HER607	HER608	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	300	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	210	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	300	400	600	800	1000	Volts
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at T _A =55℃	I _(AV)	6.0								Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	200								Amp
Maximum Forward Voltage at 6.0A and T _A =25℃	V _F	1.0			1.3		1.7			Volts
Maximum Reverse Current at T _J =25℃ at Rated DC Blocking Voltage T _J =100℃	I _R	10.0 100								uAmp
Typical Junction Capacitance (Note 1)	C _J	100					65			pF
Maximum Reverse Recovery Time (Note 2)	T _{RR}	50					75			nS
Typical Thermal Resistance (Note 3)	R _{θJA}	10								℃/W
Operating and Storage Temperature Range	T _J , T _{stg}	-55 to +150								℃

NOTES:

- 1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.
- 2- Reverse Recovery Test Conditions: I_F=.5A, I_R=1A, I_{RR}=.25A.
- 3- Thermal Resistance from Junction to Ambient at 0.375"(9.5mm) lead length P.C.B. Mounted.

HER601 THRU HER608

HIGH EFFICIENCY RECTIFIER

RATINGS AND CHARACTERISTIC CURVES

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2- MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG.3- TYPICAL REVERSE CHARACTERISTICS




FIG.5- TYPICAL FORWARD CHARACTERISTICS




FIG.4- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6- TYPICAL JUNCTION CAPACITANCE

