



JIANGSU CHANGJIANG ELECTRONICS TECHNOLOGY CO., LTD

SOT-89 Plastic-Encapsulate Transistors

KTA1664 TRANSISTOR (PNP)

FEATURES

Power dissipation

P_{CM} : 0.5 W ($T_{amb}=25^{\circ}C$)

Collector current

I_{CM} : -0.8 A

Collector-base voltage

$V_{(BR)CBO}$: -35 V

Operating and storage junction temperature range


T_J, T_{stg} : $-55^{\circ}C$ to $+150^{\circ}C$

SOT-89

1. BASE

2. COLLECTOR

3. EMITTER



ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=-1mA, I_E=0$	-35			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=-10mA, I_B=0$	-30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=-1mA, I_C=0$	-5			V
Collector cut-off current	I_{CBO}	$V_{CB}=-35V, I_E=0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB}=-5V, I_C=0$			-0.1	μA
DC current gain	$h_{FE(1)}$	$V_{CE}=-1V, I_C=-100mA$	100		320	
	$h_{FE(2)}$	$V_{CE}=-1V, I_C=-700mA$	35			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=-500mA, I_B=-20mA$			-0.7	V
Base-emitter voltage	V_{BE}	$V_{CE}=-1V, I_C=-10mA$	-0.5		-0.8	V
Transition frequency	f_T	$V_{CE}=-5V, I_C=-10mA$		120		MHz
Collector output capacitance	C_{ob}	$V_{CB}=-10V, I_E=0, f=1MHz$		19		pF

CLASSIFICATION OF $h_{FE(1)}$

Rank	O	Y
Range	100-200	160-320
Marking	RO	RY